

Quiet-Duct Commercial Series Silencers

Section 15000 Specifications

1.01 General

- A. Furnish and install "Quiet-Duct" (rectangular) silencers of the types and sizes shown on the plans and/or listed in the schedule. Silencers shall be the product of IAC Acoustics. Any specification change must be submitted in writing and approved by the Architect/Engineer, in writing, at least 10 days prior to the bid due-date.

- C. Sound attenuating units shall not fail structurally when subjected to a differential air pressure of 8 inches water gauge from inside to outside the casing. Airtight construction shall be provided by use of a duct sealing compound on the job-site material and labor furnished by the contractor.

2.01 Materials

- A. Outer casings of rectangular silencers shall be made of 22 gauge type #G-90 lock-former-quality galvanized steel.
- B. Interior partitions for rectangular silencers shall be not less than 26 gauge type #G-90 galvanized lock-former-quality perforated steel.
- C. Filler material shall be inorganic glass fiber of a proper density to obtain the specified acoustic performance and be packed under not less than 5% compression to eliminate voids due to vibration and settling. Material shall be inert, vermin- and moisture-proof.
- D. Combustion ratings for the silencer acoustic fill shall be not greater than the following when tested to ASTM E 84, NFPA Standard 255, or UL No. 723:
- | | |
|----------------------------------|----|
| Flamespread Classification | 20 |
| Smoke Development Rating..... | 20 |

4.01 Acoustic Performance

- A. All silencer ratings shall be determined in a duct-to-reverberant room test facility which provides for airflow in both directions through the test silencer in accordance with ASTM Specification E477-99. The test facility shall be NVLAP accredited for the ASTM E477-99 test standard. Data from a non-accredited laboratory will not be acceptable. The test set-up and procedure shall be such that all effects due to end reflection, directivity, flanking transmission, standing waves and test chamber sound absorption are eliminated.

Acoustic ratings shall include Dynamic Insertion Loss (DIL) and Self-Noise (SN) Power Levels both for FORWARD FLOW (air and noise in same direction) and REVERSE FLOW (air and noise in opposite directions) with airflow of at least 2000 fpm entering face velocity. Data for rectangular and tubular type silencers shall be presented for tests conducted using silencers no smaller than the following cross-sections:

Rectangular, inch: 24 x 24, 24 x 30, or 24 x 36
Tubular, inch: 12, 24, 36 and 48

3.01 Construction

- A. Units shall be constructed in accordance with the ASHRAE Guide recommendations for high pressure duct work. Seams shall be lock formed and mastic filled. Rectangular casing seams shall be in the corners of the silencer shell to provide maximum unit strength and rigidity. Interior partitions shall be fabricated from single-piece, margin-perforated sheets and shall have die-formed entrance and exit shapes so as to provide the maximum aerodynamic efficiency and minimum self-noise characteristics in the sound attenuator. Blunt noses or squared off partitions will not be accepted.
- B. Attachment of the interior partitions to the casing shall be by means of an interlocking track assembly. Tracks shall be solid galvanized steel and shall be welded to the outer casing. Attachment of the interior partitions to the tracks shall be such that a minimum of 4 thicknesses of metal exist at this location. The track assembly shall stiffen the exterior casing, provide a reinforced attachment detail for the interior partitions, and shall maintain a uniform airspace width along the length of the silencer for consistent aerodynamic and acoustic performance. Interior partitions shall be additionally secured to the outer casing with welded nose clips at both ends of the sound attenuator.

5.01 Aerodynamic Performance

- A. Static pressure loss of silencers shall not exceed those listed in the silencer schedule as the airflow indicates. Airflow measurements shall be made in accordance with ASTM specification E477-99 and applicable portions of ASME, AMCA, and ADC airflow test codes. Tests shall be reported on the identical units for which acoustic data is presented.

6.01 Certification

- A. With submittals, the manufacturer shall supply certified test data on Dynamic Insertion Loss, Self-Noise Power Levels, and Aerodynamic Performance for Reverse and Forward Flow test conditions. Test data shall be for a standard product. All rating tests shall be conducted in the same facility, shall utilize the same silencer, and shall be open to inspection upon request from the Architect/Engineer.

7.01 Duct Transitions

- A. When transitions are required to adapt silencer dimensions to connecting duct work they shall be furnished by the installing contractor.

Quiet-Duct Commercial Series Silencers

Type: LFS

Forward & Reverse Flow Ratings



The IAC Type LFS Quiet-Duct Silencers provide superior low frequency attenuation. When low frequencies are controlling, a Type LFS selection often results in a shorter silencer length than the equivalent Type S Quiet-Duct Silencer.

All LFS Silencers have been rated and certified with procedures certified in accordance with applicable portions of ASTM E4777. All Dynamic Insertion Loss and Self-Noise Acoustic Performance data were obtained in a NVLAP accredited Aero-Acoustic Laboratory using the duct-to-room reverberant test facility **with air flowing through the silencers**.

Type LFS Silencers are advantageous where low frequency DIL requirements are high in HVAC systems. In some systems, high frequency attenuation may be provided by the system components or may not be needed.

Designating Silencers

Model: 5LFS 24x18

Type: LFS **Length:** 5' **W:** 24" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+) / Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3LFS	-2000	8	14	25	29	27	20	16	12
	-1000	7	13	23	28	26	20	16	14
	0	8	13	23	28	27	21	17	14
	1000	9	12	22	28	27	21	18	14
	2000	7	11	21	25	25	21	17	14
5LFS	-2000	13	23	36	42	42	28	19	14
	-1000	13	21	35	41	41	28	21	15
	0	13	20	33	39	41	28	22	16
	1000	12	19	31	36	40	27	22	16
	2000	10	17	28	33	37	29	20	16
7LFS	-2000	14	25	40	50	51	35	22	16
	-1000	14	24	42	49	49	35	24	17
	0	13	24	40	47	47	34	25	17
	1000	12	23	37	44	45	33	25	17
	2000	10	22	37	44	45	34	24	17
10LFS	-2000	19	30	46	52	53	43	25	17
	-1000	18	32	50	52	53	45	29	19
	0	18	30	49	52	53	46	32	21
	1000	17	28	47	52	53	47	35	23
	2000	16	25	46	53	53	48	36	24

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	6 18	6 24	6 30	6 36	6 42	12 18	12 24	12 30	12 36	12 42	12 48	24 18	24 24	24 30	
3'	Wt/lb.	18	21	25	29	31	35	35	42	50	57	61	70	54	64	74
5'		29	35	42	47	52	59	58	70	83	94	104	117	89	104	121
7'		41	49	59	67	75	83	82	98	118	134	150	166	125	146	175
10'		59	70	84	95	N/A	N/A	117	140	167	190	N/A	N/A	178	209	250

Nominal Length	W/in H/in	24 36	24 42	24 48	36 18	36 24	36 30	36 36	36 42	36 48	48 18	48 24	48 30	48 36	48 42	48 48
3'	Wt/lb.	82	92	102	89	106	124	139	153	172	108	128	148	164	184	204
5'		136	152	157	147	174	204	230	256	274	178	208	242	272	304	314
7'		196	218	240	207	244	293	330	N/A							
10'		280	N/A	N/A	295	349	417	470	N/A							

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.														
		3'	0.04	0.05	0.07	0.09	0.11	0.14	0.17	0.20	0.24	0.28	0.32	0.36	0.41	0.46
LFS	5'	0.04	0.06	0.08	0.10	0.13	0.16	0.19	0.22	0.26	0.31	0.35	0.40	0.45	0.51	0.56
	7'	0.04	0.06	0.08	0.10	0.13	0.16	0.20	0.23	0.28	0.32	0.37	0.42	0.47	0.53	0.59
	10'	0.04	0.06	0.09	0.11	0.14	0.18	0.21	0.26	0.30	0.35	0.40	0.45	0.51	0.57	0.64
Silencer Face Velocity, fpm		250	300	350	400	450	500	550	600	650	700	750	800	850	900	950
		1000	1250	1500	1750	2000	2250	2500	2750	3000	3250	3500	3750	4000	4250	4500

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
LFS (all sizes)	-2000		58	54	58	61	62	62	65	63
	-1500		51	49	53	56	56	59	60	53
	-1000		45	42	45	43	45	49	44	37
	1000		46	42	45	43	45	49	44	37
	1500		56	54	57	56	52	56	57	51
	2000		68	64	65	66	61	61	64	61

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: LFM

Forward & Reverse Flow Ratings



The IAC Type LFM Quiet-Duct Silencers provide improved low frequency attenuation particularly in the third octave band. When third band performance is critical, a Type LFM Quiet-Duct selection often results in a shorter silencer length than other equivalent silencer models.

Type LFM Quiet-Duct Silencers have been rated with procedures certified in accordance with applicable portions of ASTM E477. All Dynamic Insertion Loss and Self-Noise Acoustic Performance Data were obtained in a NVLAP accredited Aero-Acoustic Laboratory using the duct-to-room reverberant test facility **with air flowing through the silencers**.

Type LFM Silencers are advantageous where low frequency, particularly third octave band, DIL requirements are high in HVAC systems. In some applications high frequency attenuation may be provided by the system components or may not be needed.

Designating Silencers

Model: 5LFM 24 x 18

Type: LFM **Length:** 5' **W:** 24" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3LFM	-2000	6	9	17	22	19	14	12	10
	-1000	6	8	16	21	18	13	12	11
	0	5	8	16	21	18	13	12	11
	1000	4	7	15	20	17	13	11	10
	2000	4	7	14	19	17	12	11	10
5LFM	-2000	9	16	26	32	29	17	13	13
	-1000	9	15	26	31	30	17	15	13
	0	9	14	25	30	29	17	15	13
	1000	8	13	23	29	28	17	14	13
	2000	7	12	22	28	28	17	14	12
7LFM	-2000	12	18	32	44	39	21	16	14
	-1000	12	18	32	43	39	21	18	15
	0	12	17	31	42	39	22	18	15
	1000	12	16	30	41	38	22	17	14
	2000	11	15	28	39	38	23	17	15
10LFM	-2000	16	24	41	51	51	26	20	16
	-1000	16	24	42	51	50	27	22	17
	0	16	23	41	51	50	28	22	17
	1000	15	22	39	50	50	28	21	16
	2000	14	20	38	50	50	28	22	17

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	6 18	6 24	6 30	6 36	6 42	12 18	12 24	12 30	12 36	12 42	12 48	24 18	24 24	24 30	
3'	Wt/lb.	18	21	25	29	31	35	35	42	50	57	61	70	54	64	74
5'		29	35	42	47	52	59	58	70	83	94	104	117	89	104	121
7'		41	49	59	67	75	83	82	98	118	134	150	166	125	146	175
10'		59	70	84	95	N/A	N/A	117	140	167	190	N/A	N/A	178	209	250

Nominal Length	W/in H/in	24 36	24 42	24 48	36 18	36 24	36 30	36 36	36 42	36 48	48 18	48 24	48 30	48 36	48 42	48 48
3'	Wt/lb.	82	92	102	89	106	124	139	153	172	108	128	148	164	184	204
5'		136	152	157	147	174	204	230	256	274	178	208	242	272	304	314
7'		196	218	240	207	244	293	330	N/A							
10'		280	N/A	N/A	295	349	417	470	N/A							

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.05	0.07	0.09	0.12	0.15	0.19	0.23	0.27	0.32	0.37	0.42	0.48	0.55	0.61	0.68
LFM	5'	0.05	0.07	0.10	0.13	0.16	0.20	0.24	0.29	0.34	0.39	0.45	0.51	0.57	0.64	0.72	0.79
	7'	0.05	0.07	0.10	0.13	0.17	0.21	0.25	0.30	0.35	0.41	0.47	0.53	0.60	0.67	0.75	0.83
	10'	0.06	0.08	0.12	0.15	0.19	0.24	0.29	0.34	0.40	0.46	0.53	0.60	0.68	0.76	0.85	0.94
	Silencer Face Velocity, fpm	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
LFM (all sizes)	-3000		64	62	64	66	65	64	66	62
	-2000		53	50	54	56	56	59	58	51
	-1000		42	40	43	45	47	46	37	27
	1000		47	34	36	35	40	37	27	20
	2000		54	52	58	56	51	56	55	50
	3000		68	64	64	63	61	63	66	63

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: S

Forward & Reverse Flow Ratings



The IAC Type S Quiet-Duct Silencers have been rated with procedures certified in accordance with applicable portions of ASTM E477. All Dynamic Insertion Loss and Self-Noise Acoustic Performance Data were obtained in a NVLAP accredited Aero-Acoustic Laboratory using the duct-to-room reverberant test facility **with air flowing through the silencers.**

Designating Silencers

Model: 5S 24x18

Type: S **Length:** 5' **Width:** 24" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3S	-2000	6	12	20	33	39	35	23	14
	-1000	5	11	17	33	38	35	25	14
	0	5	10	16	32	38	35	26	16
	1000	5	9	15	30	37	35	27	17
	2000	5	8	14	27	36	35	27	17
5S	-2000	10	20	27	45	48	43	36	22
	-1000	10	19	26	44	47	45	38	22
	0	9	17	25	43	47	46	39	24
	1000	7	17	23	42	46	46	40	25
	2000	6	16	22	40	46	46	40	25
7S	-2000	12	23	37	48	50	45	41	27
	-1000	12	22	35	47	49	47	44	28
	0	11	20	33	47	49	47	45	31
	1000	9	18	31	47	49	47	45	34
	2000	8	16	31	46	49	48	45	35
10S	-2000	14	26	43	50	51	50	45	37
	-1000	14	28	42	49	51	50	49	37
	0	13	25	42	49	52	50	49	41
	1000	12	22	41	49	52	50	49	44
	2000	11	19	40	50	52	50	49	46

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	6 18	6 24	6 30	6 36	6 42	12 18	12 24	12 30	12 36	12 42	12 48	24 N/A	24 18	24 24	24 30
3'	Wt/lb.	25	35	42	49	60	70	43	52	62	74	83	93	71	86	102
5'		44	63	75	87	105	126	73	89	107	125	141	158	121	147	173
7'		61	88	102	122	147	176	102	125	150	176	199	226	170	207	243
10'		86	123	150	171	206	246	155	177	212	250	N/A	N/A	241	293	345

Nominal Length	W/in H/in	24 36	24 42	24 48	36 18	36 24	36 30	36 36	36 42	36 48	48 18	48 24	48 30	48 36	48 42	48 48
3'	Wt/lb.	117	132	147	81	102	142	162	182	204	142	172	204	234	264	294
5'		204	230	256	142	177.5	249	284	319	355	242	294	346	408	460	512
7'		288	325	362	207	244	293	330	N/A	N/A	340	414	486	576	650	724
10'		405	N/A	482	586	690	810	N/A	N/A							

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.01	0.03	0.06	0.09	0.13	0.18	0.23	0.29	0.36	0.44	0.52	0.61	0.71	0.82	0.93
S	5'	0.02	0.04	0.07	0.10	0.15	0.20	0.26	0.33	0.41	0.49	0.59	0.69	0.80	0.91	1.04	1.17
S	7'	0.02	0.04	0.07	0.11	0.16	0.21	0.28	0.35	0.44	0.53	0.63	0.74	0.85	0.98	1.11	1.26
S	10'	0.02	0.04	0.08	0.12	0.18	0.24	0.32	0.40	0.49	0.60	0.71	0.83	0.97	1.11	1.26	1.43
Silencer Face Velocity, fpm		200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
S (all sizes)	-2000		68	62	61	66	61	64	67	66
	-1000		54	51	50	51	54	56	52	40
	-500		40	40	39	36	47	48	37	20
	500		36	29	35	30	31	35	22	20
	1000		55	49	49	47	46	49	42	32
	2000		74	69	63	64	61	63	62	56

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: ES

Forward & Reverse Flow Ratings



The IAC Type ES Quiet-Duct Silencers have been rated with procedures certified in accordance with applicable portions of ASTM E477. All Dynamic Insertion Loss and Self-Noise Acoustic Performance Data were obtained in a NVLAP accredited Aero-Acoustic Laboratory using the duct-to-room reverberant test facility **with air flowing through the silencers**.

For many years, the IAC Type S Quiet-Duct Silencer has been the industry standard for maximum noise reduction with minimum silencer length. The Type ES ("Energy Saver") Silencer provides the same high level of acoustic performance combined with a marked decrease in energy consumption.

Designating Silencers

Model: 5ES 24x18

Type: ES **Length:** 5' **Width:** 24" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3ES	-2000	5	8	18	31	38	36	22	16
	-1000	3	8	17	31	38	36	22	17
	0	3	6	16	29	38	35	22	18
	1000	2	5	14	27	36	34	23	17
	2000	2	5	12	25	34	34	23	18
5ES	-2000	10	16	25	41	52	48	26	17
	-1000	10	15	24	40	50	50	31	20
	0	9	12	22	38	51	50	33	22
	1000	7	12	19	37	51	49	35	23
	2000	6	12	19	35	49	49	35	24
7ES	-2000	11	20	39	53	51	53	37	21
	-1000	11	21	36	51	53	53	43	25
	0	10	19	33	50	53	53	46	29
	1000	7	16	31	50	53	52	46	32
	2000	6	15	29	48	54	50	48	34
10ES	-2000	15	31	40	53	54	53	43	24
	-1000	13	33	44	51	51	53	48	26
	0	11	28	43	52	52	53	49	32
	1000	9	25	41	52	51	54	49	37
	2000	7	24	38	53	51	54	50	39

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	6 18	6 24	6 30	6 36	6 42	12 18	12 24	12 30	12 36	12 42	12 48	24 N/A	24 18	24 24	24 30
3'	Wt/lb.	25	35	42	49	60	70	43	52	62	74	83	93	71	86	102
5'		44	63	75	87	105	126	73	89	107	125	141	158	121	147	173
7'		61	88	102	122	147	176	102	125	150	176	199	226	170	207	243
10'		86	123	150	171	206	246	155	177	212	250	N/A	N/A	241	293	345

Nominal Length	W/in H/in	24 36	24 42	24 48	36 18	36 24	36 30	36 36	36 42	36 48	48 18	48 24	48 30	48 36	48 42	48 48
3'	Wt/lb.	117	132	147	81	102	142	162	182	204	142	172	204	234	264	294
5'		204	230	256	142	177.5	249	284	319	355	242	294	346	408	460	512
7'		288	325	362	207	244	293	330	N/A	N/A	340	414	486	576	650	724
10'		405	N/A	482	586	690	810	N/A	N/A							

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.01	0.02	0.04	0.06	0.08	0.11	0.14	0.18	0.22	0.27	0.32	0.37	0.43	0.50	0.57
ES	5'	0.01	0.02	0.04	0.06	0.09	0.12	0.15	0.19	0.24	0.29	0.34	0.40	0.46	0.53	0.60	0.68
	7'	0.01	0.03	0.05	0.08	0.12	0.17	0.22	0.28	0.34	0.41	0.49	0.57	0.67	0.76	0.87	0.98
	10'	0.02	0.04	0.07	0.11	0.16	0.22	0.28	0.36	0.44	0.54	0.64	0.75	0.87	1.00	1.13	1.28
	Silencer Face Velocity, fpm	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
ES (all sizes)	-2000		56	54	58	60	61	65	69	64
	-1500		47	47	52	55	57	63	64	54
	-1000		41	41	45	47	52	60	48	38
	1000		42	35	33	32	34	33	27	22
	1500		50	47	44	41	43	45	43	41
	2000		60	57	54	50	49	53	53	50

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: MS

Forward & Reverse Flow Ratings



The IAC Type MS Quiet-Duct Silencers have been rated with procedures certified in accordance with applicable portions of ASTM E477. All Dynamic Insertion Loss and Self-Noise Acoustic Performance Data were obtained in a NVLAP accredited Aero-Acoustic Laboratory using the duct-to-room reverberant test facility **with air flowing through the silencers.**

The IAC Type MS Silencers provide superior performance with mid-range frequency from third thru sixth octave bands, where DIL have specific requirements in HVAC systems. In some applications high frequency attenuation may be provided by the system components or may not be needed.

Designating Silencers

Model: 5MS 30x18

Type: MS **Length:** 5' **Width:** 30" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3MS	-4000	5	7	14	24	27	20	12	9
	-2000	6	7	13	24	26	19	13	9
	0	5	7	13	23	25	20	15	10
	2000	4	6	12	21	24	21	16	11
	4000	3	5	11	18	23	22	17	11
5MS	-4000	7	12	21	38	43	32	19	10
	-2000	5	10	19	36	43	31	19	10
	0	5	10	18	35	43	32	21	12
	2000	4	9	17	34	42	33	22	14
	4000	3	8	16	32	40	34	22	15
7MS	-4000	8	17	28	41	46	41	24	13
	-2000	7	14	25	42	50	40	24	13
	0	7	14	24	42	50	42	26	15
	2000	7	13	23	41	49	44	28	17
	4000	6	11	21	40	49	45	30	19
10MS	-4000	12	21	35	43	52	47	31	18
	-2000	11	19	34	45	52	50	33	17
	0	11	18	33	45	52	51	36	19
	2000	10	17	32	45	51	52	38	21
	4000	9	14	29	44	48	50	40	23

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	7.5 18	7.5 24	7.5 30	7.5 36	7.5 42	7.5 48	15 18	15 24	15 30	15 36	15 42	15 48	30 18	30 24	30 30
3'	Wt/lb.	26	40	45	51	66	80	47	57	67	80	89	100	80	95	110
5'		46	67	80	91	112	134	80	96	114	134	150	167	135	161	187
7'		65	95	100	129	158	190	112	135	159	193	216	240	188	224	261
10'		90	135	157	180	223	270	159	192	226	273	N/A	N/A	220	319	371

Nominal Length	W/in H/in	30 36	30 42	30 48	45 18	45 24	45 30	45 36	45 42	45 48	60 18	60 24	60 30	60 36	60 42	60 48
3'	Wt/lb.	130	145	160	127	152	156	177	197	218	160	190	220	260	290	320
5'		22	248	274	215	257	275	310	345	381	270	322	374	44	496	548
7'		310	347	384	300	359	N/A	N/A	N/A	N/A	376	448	522	620	694	768
10'		440	N/A	440	638	742	880	N/A	N/A							

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.06	0.08	0.10	0.12	0.14	0.17	0.20	0.23	0.26	0.29	0.33	0.36	0.40	0.44	0.49
MS	5'	0.08	0.10	0.12	0.15	0.17	0.20	0.24	0.27	0.31	0.35	0.39	0.44	0.48	0.53	0.58	0.64
	7'	0.10	0.12	0.15	0.18	0.22	0.26	0.30	0.34	0.39	0.44	0.49	0.54	0.60	0.67	0.73	0.80
	10'	0.12	0.15	0.19	0.23	0.27	0.31	0.36	0.42	0.48	0.54	0.60	0.67	0.74	0.82	0.90	0.98
	Silencer Face Velocity, fpm	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
MS (all sizes)	-3000		67	63	61	66	61	64	67	67
	-2000		60	56	56	56	57	59	58	49
	-1000		46	45	45	41	50	51	43	23
	1000		44	32	36	34	31	32	29	21
	2000		63	54	52	50	47	48	47	44
	3000		74	64	60	58	56	58	59	57

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: LFL

Forward & Reverse Flow Ratings



The IAC Type LFL Quiet-Duct Silencers provide improved low frequency attenuation as well as low pressure drop aerodynamic performance. When third and fourth band performance is critical at the lowest available pressure drop, a Type LFL Quiet-Duct selection often results in a shorter silencer length than other equivalent silencer models.

Type LFL Quiet-Duct Silencers have been rated with procedures certified in accordance with applicable portions of ASTM E477. All Dynamic Insertion Loss and Self-Noise Acoustic Performance Data were obtained in a NVLAP accredited Aero-Acoustic Laboratory using the duct-to-room reverberant test facility **with air flowing through the silencers**.

Type LFL Silencers are advantageous where low frequency acoustic performance and low pressure drop aerodynamic performance are both essential to the HVAC system. In many applications higher frequency attenuation is provided by the system components or may not be needed.

Designating Silencers

Model: 5LFL 24x18

Type: LFL **Length:** 5' **Width:** 24" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3LFL	-2000	5	7	14	17	17	11	12	10
	-1000	4	7	13	17	17	11	11	10
	0	4	8	14	19	19	13	11	10
	1000	4	8	14	20	20	15	11	10
	2000	4	8	13	19	20	12	11	9
5LFL	-2000	6	12	19	27	28	15	15	13
	-1000	7	12	19	27	27	15	14	13
	0	7	11	18	26	26	15	13	12
	1000	6	10	17	24	25	14	12	11
	2000	5	10	16	23	25	14	12	11
7LFL	-2000	9	15	25	38	32	17	15	13
	-1000	9	14	24	38	32	17	15	14
	0	8	13	23	38	32	17	15	14
	1000	7	12	22	37	31	17	15	13
	2000	6	12	20	36	31	18	14	13
10LFL	-2000	12	20	32	43	42	20	18	15
	-1000	11	19	32	44	42	21	17	15
	0	11	18	31	44	42	21	17	15
	1000	10	17	29	44	41	21	17	15
	2000	9	16	27	44	41	21	16	15

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	6 18	6 24	6 30	6 36	6 42	12 18	12 24	12 30	12 36	12 42	12 48	24 18	24 24	24 30	
3'	Wt/lb.	18	21	25	29	31	35	35	42	50	57	61	70	54	64	74
5'		29	35	42	47	52	59	58	70	83	94	104	117	89	104	121
7'		41	49	59	67	75	83	82	98	118	134	150	166	125	146	175
10'		59	70	84	95	N/A	N/A	117	140	167	190	N/A	N/A	178	209	250

Nominal Length	W/in H/in	24 36	24 42	24 48	36 18	36 24	36 30	36 36	36 42	48 18	48 24	48 30	48 36	48 42	48 48	
3'	Wt/lb.	82	92	102	89	106	124	139	153	172	108	128	148	164	184	204
5'		136	152	157	147	174	204	230	256	274	178	208	242	272	304	314
7'		196	218	240	207	244	293	330	N/A	N/A						
10'		280	N/A	N/A	295	349	417	470	N/A	N/A						

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.01	0.05	0.08	0.11	0.15	0.19	0.24	0.30	0.36	0.43	0.51	0.59	0.68	0.77	0.87
LFL	5'	0.01	0.05	0.08	0.12	0.16	0.20	0.26	0.32	0.39	0.46	0.54	0.63	0.72	0.82	0.92	1.04
	7'	0.01	0.05	0.09	0.12	0.17	0.22	0.28	0.34	0.41	0.49	0.57	0.67	0.77	0.87	0.98	1.10
	10'	0.02	0.06	0.10	0.14	0.19	0.24	0.31	0.38	0.46	0.55	0.64	0.74	0.86	0.97	1.10	1.23
Silencer Face Velocity, fpm		400	800	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
LFL (all sizes)	-3000		55	54	56	57	56	59	61	56
	-2000		46	45	48	49	50	54	49	42
	-1000		31	30	34	35	40	45	28	20
	1000		32	24	32	25	34	39	24	20
	2000		47	42	46	44	46	51	46	38
	3000		56	53	54	55	53	58	59	53

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: ML

Forward & Reverse Flow Ratings



The IAC Type ML Quiet-Duct Silencers provide improved medium-low frequency attenuation as well as low pressure drop aerodynamic performance. When fourth and fifth band performance is critical at the lowest available pressure drop, a Type ML Quiet-Duct selection often results in a shorter silencer length than other equivalent silencer models.

Designating Silencers

Model: 5ML 36x18

Type: ML **Length:** 5' **Width:** 36" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3ML	-5000	4	5	12	20	18	11	7	5
	-2000	3	5	10	19	18	12	8	6
	0	3	5	10	19	18	12	9	7
	2000	3	4	9	18	17	12	9	8
	5000	2	4	8	16	17	13	10	9
5ML	-5000	6	9	18	32	32	17	9	6
	-2000	5	8	16	31	31	17	10	7
	0	5	8	15	31	31	19	12	9
	2000	4	7	14	30	30	20	13	10
	5000	3	6	14	28	29	22	13	11
7ML	-5000	6	12	22	42	43	24	14	10
	-2000	6	11	21	41	40	23	15	10
	0	6	11	20	39	40	25	16	11
	2000	5	10	19	37	39	26	16	12
	5000	5	9	17	36	38	28	16	12
10ML	-5000	9	18	28	46	47	34	19	11
	-2000	8	17	27	47	50	33	20	12
	0	8	16	26	46	50	35	20	12
	2000	7	15	25	45	49	36	20	12
	5000	7	15	23	44	50	36	21	14

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	9 18	9 24	9 30	9 36	9 42	18 18	18 24	18 30	18 36	18 42	18 48	36 18	36 24	36 30	
3'	Wt/lb.	35	41	52	57	65	73	52	61	71	84	94	101	69	103	120
5'		60	71	82	95	107	119	87	103	121	142	158	175	120	175	201
7'		84	100	116	133	150	167	122	144	168	200	223	247	169	246	283
10'		118	141	167	190	240	215	174	205	239	284	N/A	N/A	238	349	403

Nominal Length	W/in H/in	36 36	36 42	36 48	54 18	54 24	54 30	54 36	54 42	54 48	72 18	72 24	72 30	72 36	72 42	72 48
3'	Wt/lb.	138	153	168	121	164	191	222	247	272	138	206	240	276	306	336
5'		239	265	291	207	278	322	381	423	466	239	350	402	478	530	582
7'		337	374	411	291	390	451	537	597	658	337	492	566	674	748	822
10'		475	N/A	N/A	412	554	642	759	N/A	N/A	475	698	806	950	N/A	N/A

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.05	0.07	0.10	0.13	0.16	0.20	0.24	0.28	0.33	0.38	0.44	0.50	0.57	0.64	0.71
ML	5'	0.06	0.08	0.12	0.15	0.19	0.24	0.28	0.34	0.40	0.46	0.53	0.60	0.68	0.76	0.85	0.94
	7'	0.07	0.11	0.14	0.19	0.24	0.29	0.36	0.42	0.50	0.58	0.66	0.75	0.85	0.95	1.06	1.18
	10'	0.09	0.13	0.18	0.23	0.29	0.36	0.44	0.52	0.61	0.71	0.82	0.93	1.05	1.18	1.31	1.45
	Silencer Face Velocity, fpm	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600	3800	4000

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
ML (all sizes)	-3000		64	59	59	63	60	62	63	59
	-2000		56	53	52	53	56	58	52	44
	-1000		42	42	41	38	49	50	37	20
	1000		39	35	30	27	26	28	28	20
	2000		58	52	46	43	42	45	45	39
	3000		71	61	55	53	51	55	56	52

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes

Quiet-Duct Commercial Series Silencers

Type: L

Forward & Reverse Flow Ratings



The IAC Type L Quiet-Duct Silencers provide excellent frequency attenuation as well as low pressure drop aerodynamic performance. When fifth and sixth band performance is critical at the lowest available pressure drop, a Type L Quiet-Duct selection often results in a shorter silencer length than other equivalent silencer models.

Designating Silencers

Model: 5L 24x18

Type: L **Length:** 5' **Width:** 24" **Height:** 18"

Table I: Dynamic Insertion Loss (DIL) Ratings: Forward (+)/Reverse (-) Flow

IAC Model	Octave Band	1	2	3	4	5	6	7	8
	Hz	63	125	250	500	1K	2K	4K	8K
	Face Velocity, fpm	Dynamic Insertion Loss, dB							
3L	-5000	4	7	10	16	23	18	12	7
	-2000	3	5	9	15	22	19	12	8
	0	3	5	9	15	22	21	13	9
	2000	3	5	8	14	21	22	13	9
	5000	2	4	7	13	19	22	14	10
5L	-5000	6	10	15	25	33	32	16	9
	-2000	5	8	14	24	32	32	16	10
	0	5	8	14	23	31	34	17	12
	2000	5	7	13	22	30	35	18	13
	5000	4	6	11	20	28	35	19	13
7L	-5000	7	15	20	33	42	39	21	12
	-2000	6	12	18	31	42	40	20	13
	0	6	12	17	30	41	42	21	14
	2000	6	11	16	29	39	43	22	15
	5000	5	8	15	28	37	43	24	16
10L	-5000	9	20	28	44	47	46	28	16
	-2000	9	16	25	42	48	48	28	17
	0	9	15	24	41	48	49	29	19
	2000	9	14	23	40	48	49	29	20
	5000	8	12	21	39	47	49	32	22

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99. Contact IAC if attenuation in excess of 50 dB is required.

Table II: Weights & Measures

Nominal Length	W/in H/in	6 18	6 24	6 30	6 36	6 42	12 18	12 24	12 30	12 36	12 42	12 48	24 N/A	24 18	24 24	24 30
3'	Wt/lb.	29	35	42	49	56	63	43	52	62	74	83	93	71	86	102
5'		52	63	75	87	99	111	73	89	107	125	141	158	121	147	173
7'		72	88	105	122	139	156	102	125	150	176	199	226	170	207	243
10'		101	123	147	171	163	187	155	177	212	25	N/A	N/A	241	293	345

Nominal Length	W/in H/in	24 36	24 42	24 48	36 18	36 24	36 30	36 36	36 42	36 48	48 18	48 24	48 30	48 36	48 42	48 48
3'	Wt/lb.	117	132	147	101	121	143	163	184	205	140	168	182	209	235	261
5'		204	230	256	180	211	245	279	312	346	242	284	312	353	395	438
7'		288	325	362	252	295	351	398	445	492	N/A	N/A	N/A	N/A	N/A	N/A
10'		405	N/A													

Table III: Aerodynamic Performance

IAC Model	L/Ft	Static Pressure Drop, i.w.g.															
		3'	0.05	0.07	0.10	0.13	0.16	0.20	0.24	0.29	0.34	0.39	0.45	0.51	0.58	0.65	0.72
L	5'	0.06	0.08	0.11	0.14	0.18	0.22	0.27	0.32	0.37	0.43	0.50	0.56	0.64	0.71	0.79	0.88
L	7'	0.06	0.09	0.12	0.15	0.19	0.24	0.29	0.35	0.41	0.47	0.54	0.61	0.69	0.78	0.87	0.96
L	10'	0.07	0.10	0.13	0.17	0.22	0.27	0.33	0.39	0.46	0.53	0.61	0.69	0.78	0.87	0.97	1.08
Silencer Face Velocity, fpm		1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600	3800	4000

Table IV: Self-Noise Power Levels, dB re: 10-12 Watts

IAC Model	Octave Band		1	2	3	4	5	6	7	8
	Hz		63	125	250	500	1K	2K	4K	8K
	Silencer Face Velocity, fpm									
L (all sizes)	-3000		64	59	58	62	60	62	62	58
	-2000		55	52	52	53	56	56	56	43
	-1000		41	41	41	38	49	48	38	20
	1000		38	31	37	32	32	36	24	20
	2000		57	51	51	49	47	50	44	35
	3000		68	63	59	60	56	58	56	50

(+) Forward Flow / (-) Reverse Flow. Aero-acoustic performance data based on NVLAP accredited laboratory tests conducted in strict accordance with ASTM E477-99.

TAKE NOTE!

- Silencer Face Area is the cross-sectional area at the silencer entrance
- Face Velocity is the CFM of airflow divided by the Face Area (in sq. ft.)
- Pressure Drop for any velocity can be calculated from this equation:

$$PD = (\text{Actual FV}/\text{Catalog FV})^2 \times (\text{Catalog PD})$$
- Self Noise values shown are for a four-square-foot face area silencer
- For each doubling of the face area add 3 dB to the self-noise values listed
- For each halving of the face area subtract 3 dB from the self-noise values listed
- Weights and measures are listed for limited number of available sizes